

# Wallgard



HOMOGENEOUS WALLCOVERING

VINYL



- > Impervious surface with PU-Shield
- > Hygienic and watertight
- > Easy to install – vertically or horizontally
- > Attractive and functional design



## Optimum qualities for walls

# Vinyl wallcovering

Wallgard wallcovering is the perfect solution for areas that need special protection, not only in wet rooms but also in other environments like healthcare and light industry. The classic design makes Wallgard a good choice for areas that are intended to feel modern and functional for many years to come.

It is also colour co-ordinated with Tarkett's top-quality range of homogeneous vinyl floorings, giving the freedom to create the right look for the whole area.

### Homogeneous wall product

Wallgard is a homogeneous vinyl product that has been developed to suit all wall conditions. For example, it meets all fire regulations for walls.

It is manufactured from watertight and extremely hardwearing high-quality vinyl. The homogeneous construction makes it durable against mechanical damage and allows easy repair.

### New and unique surface

The polyurethane-coated surface, PU-Shield, is unique and makes the wall very easy to maintain, because almost nothing adheres to it. The important issue of hygiene is therefore well taken care of. Wallgard enhances protection against fungi and bacteria, and its performance meets the stringent requirements imposed in environments such as healthcare and industry. Wallgard's plasticity and 1.3 mm thickness make it safer and easier to install.

It can be applied vertically or horizontally. All joints are heat-welded to give a completely watertight finish.

The overall ease of installation and its long service life give Wallgard a competitive life cycle cost.





## Safe installation

Tarkett have more than 50 years' experience of manufacturing floor and wall coverings.

We offer a tried and trusted formula – a system of products, accessories and installation instructions to guarantee a watertight, hygienic and attractive area. Wallgard wallcovering is a part of this system, and is ideal for use in hospitals, schools, retirement homes, sports centres, hostels, rehabilitation centres, clean room areas and the pharmaceutical and food industries. Of course, correct installation guarantees perfect results.

### Joint seams

The wallcovering's joints must be sealed using heat welding. This method gives very durable and completely watertight joints. The wall can even be regularly cleaned using high-pressure washing techniques.

### Welding

A rod in the same material is heated in contact with the wallcovering. The result is that the two melt together and make a very strong joint.

### Cutting

The excess material after welding is trimmed in two steps, producing a completely even surface that is flush with adjoining material.

### Ceiling joints

The wallcovering can also be installed over the ceiling. A profile is sometimes used at the junction between wall and ceiling to increase the radius, which facilitates installation and future cleaning.





*CNB - Centro Nacional de Bio-tecnología, Madrid*



CNB, Madrid  
Lundbeck, Denmark  
BMC, Uppsala University



## Covering walls and floors all over the world **Solutions by Tarkett**

For people to feel comfortable in a room, there are several important factors. The wall and floor coverings may not be perceived as critical. However, they should be chosen very carefully with regard to their aesthetics, function and economy. Our 30 years' experience in developing wall and floor coverings means we can offer products that meet high expectations in many ways. Solutions from Tarkett are popular choices for architects, engineers and contractors all over the world.



*Nijmegen Hospital, NL*



*H. Lundbeck A/S, Denmark*



*Spallanzani Hospital, Rome*



*H. Lundbeck A/S, Denmark*

# Wallgard by Tarkett

## Attractive and harmonious

### Vertical installation

Wallcoverings from Tarkett can be applied vertically (the most common) or horizontally, depending on the desired pattern effect or technical specification. The wallcovering is fitted to overlap the flooring, and joints are heat-welded to give a completely watertight finish. Installation should be carried out by a qualified specialist.




### Horizontal installation

The wallcovering can be applied horizontally, which is quicker and reduces the number of joints. This is an advantage in highly water-sensitive areas such as shower rooms or corridors. Any gap between the ceiling and the wallcovering is concealed with a matching border. Installation should be carried out by a qualified specialist.



# design




011

NCS S 0500-N  
Welding Rod No. 1290 011



012

NCS S 1000-N  
Welding Rod No. 1288 124




013

NCS S 1002-Y50R  
Welding Rod No. 1290 013



014

NCS S 0510-Y30R  
Welding Rod No. 1288 907



015

NCS S 1005-B50G  
Welding Rod No. 1290 015



016

NCS S 1010-R80B  
Welding Rod No. 1290 016

**Wallgard vinyl wallcovering is an excellent choice for areas that need special protection, not only in wet rooms but also in other environments related to healthcare and industry.**

- PU-Shield polyurethane surface treatment offers many unique advantages:
  - seals the surface and makes it impervious and dirt-repelling
  - better appearance with lustrous and fresh-looking surface
  - fewer friction marks from wheelchairs and beds
  - easy maintenance due to smooth surface
  - good hygienic properties due to minimal risk of bacterial and fungal growth
  - easier installation because dirt and glue don't adhere to the product
- The product's thickness simplifies installation and makes welded joints more durable
- Sturdy enough to withstand heavy corridor traffic in healthcare and school areas



# Wallgard

Homogeneous heavy duty wallcovering. Unique PU-Shield surface for better hygiene and cleanliness. Subtle and discreet design in modern colours. Can be installed vertically or horizontally. Heat welded seams with colour co-ordinated rods.

Technical data		WALLGARD
Type of wallcovering		Homogeneous vinyl wallcovering
Wear layer thickness	EN 429	1.3 mm
Surface treatment		PU-Shield
Total thickness	EN 428	1.3 mm
Total weight/m <sup>2</sup>	EN 430	2210 kg
Dimensional stability	EN 434	≤ 0.40 %
Wetroom test	GBR Class VT	approved
Reaction to fire	EN ISO 13501-1 NFP 92-501 BS 476: Part 7 AS/NZS 3837 UNI 8457 ASTM E84	Class B s2 d0 test in progress Class 1 Class B Class 1 Class B
Light fastness	EN ISO 105-B02	≥ 6
Chemical resistance	EN 423	good resistance
Fungi and Bacterial resistance	DIN EN ISO 846-A/C	does not favour growth
Clean room test	ASTM F24/65 ASTM F51/00	satisfactory Class A
Colours		6
Form of delivery	EN 426 Sheet (rolls)	approx. 30 running metres x 200 cm art. no. 3388 _ _ _ <small>3 digit colour number</small>

Wallgard	Welding Rod No.
011	1290 011
012	1290 124
013	1290 013
014	1290 907
015	1290 015
016	1290 016

Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for these instructions.

*The above information is subject to modification for the benefit of further improvement (08/06). For more detailed technical information, please contact Tarkett.*



## TARKETT SALES COMPANIES

[www.tarkett-commercial.com](http://www.tarkett-commercial.com)

**Australia:** Tarkett Australia Pty Ltd – Tel. +61 2 96 34 73 73 • **Austria:** Tarkett AG Niederlassung Wien – Tel. +43 1 47 88 062 • **Baltic States:** Tarkett SAS – Tel. +370 37 262 220 • **Belgium:** S.A. Tarkett NV – Tel. +32 2 520 04 67 • **China:** Tarkett Asia Pacific Limited Shanghai Representative Office – Tel. +86 (21) 62 88 15 38 • **Czech Republic:** Tarkett SAS, org. slozka – Tel. +420-271 001 602 • **Denmark:** Tarkett A/S – Tel. +45 43 90 60 11 • **Finland:** Tarkett Oy – Tel. +358 9 5406 5870 • **France:** Tarkett SAS – Tel. +33 1 41 20 42 49 • **Germany:** Tarkett AG, Bereich Objekt – Tel. +49 6233 810 • **Greece:** Tarkett Monoprosopi Ltd – Tel. +30 2 10 576 3889 • **Hong Kong:** Tarkett Asia Pacific Ltd. – Tel. +852 2511 8716 • **Hungary:** Tarkett SAS – Tel. +36 1 437-8150 • **Italy:** Tarkett S.p.A. – Tel. +39 02 893 411 • **Luxembourg:** Tel. +352 949 211 8804 • **Middle East:** Tarkett Middle East – Tel. +961 1 75 2363/4 • **Netherlands:** Tarkett Benelux B.V. – Tel. +31 76 57 80 760 • **Norway:** Tarkett AS – Tel. +47 32 20 92 00 • **Poland:** Tarkett Sp. z o.o – Tel. +48 22 598 08 81 • **Portugal:** Tarkett SA – Tel. +351 21 427 64 20 • **Russian Federation:** Tarkett Russia – Tel. +7 4 95 777 69 83 • **Slovakia:** Tarkett SAS – Tel. +421 37 6515 404 • **Singapore:** Tarkett Far East – Tel. +65 6743 53 84 • **South East Europe:** Tarkett Trade d.o.o. – Tel. +381 21 7557 649 • (44) 569 12 21 • **United Kingdom:** Tarkett-Marley Floors Limited – Tel. +44 (0) 1622 854 040 • **Spain:** Tarkett Floors S.L – Tel. +34 91 358 00 35 • **Sweden:** Tarkett Sverige AB – Tel. +46 771 25 19 00 • **Switzerland:** Tarkett AG, Bereich Objekt Schweiz – Tel. +41 043 233 79 24 • **Ukraine:** Tarkett UA – Tel. +380380 (44) 569 12 21 • **USA/Canada:** Tarkett Inc. USA – Tel. +1 713 869 5811 • Johnsonite – Tel. +1 440 543 8916 • **Tarkett International:** Tel. +49 6233 811 755 – Tel. +33 41 20 41 01